



2925 Galleria Drive, Arlington, TX 76011

March 3, 2008

## GENERAL MATERIAL CERTIFICATION LETTER

For the purpose of LEED documentation only, we certify that the following products contain:

Product name	Description
<b>SEALECTION 500<sup>®</sup></b>	Spray Polyurethane Foam <b>Section 07216</b> (2004 Master format <b>Section 07 21 19</b> )

MR 2.1 **CONSTRUCTION WASTE MANAGEMENT**  
2.2 Construction waste on site: negligible, protection material only

MR 5.1 **REGIONAL MATERIAL**  
5.2 Manufactured On-Site

QEI 4.1 **INDOOR ENVIRONMENTAL QUALITY**  
**SEALECTION 500<sup>®</sup>** content:  
0% FORMALDEHYDE, 0% CFC, 0% HCFC, 0% HFC, 0% Hydrocarbons

*SEALECTION 500<sup>®</sup> is a two component, open-celled, spray-applied, semi-rigid polyurethane foam system. This product is a fully water blown system having a low in-place density which can contribute significantly to the energy efficiency of the building. The application of SEALECTION 500<sup>®</sup> spray foam insulation offers a substantial reduction of air infiltration and improved integrity of the air tightness allowing for more accurate sizing of the HVAC which is generally smaller in tonnage.*

Dave Lall  
Vice President, General Manager  
DEMILEC USA LLC